

## OMNIPRO MOLD RESISTANT BARRIER WARNING



### May cause an allergic skin reaction.

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace.

**Response: IF ON SKIN:** Wash with plenty of soap and water. **If skin irritation or rash occurs:** Get medical advice/attention. Wash contaminated clothing before reuse.

**Storage:** Keep/Store away from clothing/combustible materials.

**Disposal:** Dispose of contents/container to an approved waste disposal plant.

**Contains:** MIXTURE OF 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2 H-ISOTHIAZOL-3-ONE (3:1) May produce an allergic reaction.

**Emergency: 800-535-5053**  
Read SDS at [www.omniprorestoration.com](http://www.omniprorestoration.com)

Net Contents: 5 Gal (18.9 L)

Patented product of Kop-Coat, Inc. Manufactured expressly for:



OmniPro Restoration 4282 South 590 West, Salt Lake City, Utah 84123 (800) 637-3789



# OMNIPRO



# MOLD RESISTANT BARRIER

## PENETRATING MOLD- AND MILDEW-RESISTANT BARRIER\*

pH: 8.2

\*Provides mold and mildew resistance on the dry coating film.

**Net Contents: 5 Gallons (18.9 L) REORDER#: 1671-5346**

**FOR PROFESSIONAL USE ONLY. READY TO USE. DO NOT DILUTE.**

### DIRECTIONS:

- 1) HEPA vacuum surface.
- 2) Apply OmniPro Mold Stain Remover (1674-5349) per label directions and allow to dry completely.
- 3) Remove loose organic material by HEPA vacuuming surface again.
- 4) For extended protection from mold and mildew growth, apply OmniPro Mold Resistant Barrier to treated surfaces.

OmniPro Mold Resistant Barrier's unique penetrating barrier is highly effective as a final step on mold stain removal jobs. OmniPro Mold Resistant Barrier is a new class of mold- and mildew-resistant coating\* that works by restraining nutrients that promote mold and mildew growth from reaching the surface, helping give peace of mind to contractors and building owners.

### OMNIPRO MOLD RESISTANT BARRIER'S PATENTED TECHNOLOGY DELIVERS:

- Breathable barrier that allows water to evaporate out of wood while blocking mold-supporting nutrients from migrating to the surface
- EPA-registered preservative to inhibit growth of mold and mildew on the dry surface coating
- Added protection against future water damage and staining from mold and mildew
- Economical, water-thin, low-VOC solution that can be applied with airless sprayer

### RECOMMENDED APPLICATIONS:

For use on construction surfaces, such as OSB, plywood, other engineered wood products, brick, and wallboard. Do not over apply to load bearing I-joists with OSB webbing.

### OMNIPRO MOLD RESISTANT BARRIER INSTRUCTIONS:

Ready to use, do not dilute prior to use. Stir OmniPro Mold Resistant Barrier thoroughly then apply as final step in the mold stain removal process. Do not mix or use any other products with OmniPro Mold Resistant Barrier. Apply at the rate of 250-1,000 sq ft per gallon (6-24 square meters/liter) depending on surface porosity.

### APPLICATION EQUIPMENT:

Airless sprayer, brush or paint roller. If using airless sprayer, avoid atomizing the solution by using a tip with no smaller than a 0.515 orifice. All surfaces must be treated to provide a mold- and mildew-resistant coating.\*

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

\*Provides mold and mildew resistance on the dry coating film.

© 2017 Made in U.S.A.  
L.13130 Rev (A)

