

MOLD STAIN REMOVER DANGER



Causes severe skin burns and eye damage.

Prevention: Do not breathe dusts or mists. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response: Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

More detailed First Aid measures may be found in Section 4 of the SDS.

Storage: Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Emergency: 800-535-5053

Read SDS at www.omniprestoration.com

Net Contents: 1 Gal (3.8 L)

Manufactured expressly for:



OmniPro Restoration 4282 South 590 West, Salt Lake City, Utah 84123 (800) 637-3789



OMNI PRO



MOLD STAIN REMOVER

**FOAMING OXIDIZING CLEANER THAT REMOVES SOILS
AND STAINS CAUSED BY MOLD AND MILDEW**

pH: 4.5

Net Contents: 1 Gallon (3.8 L) REORDER#: 1674-5349

FOR PROFESSIONAL USE ONLY. READY TO USE. DO NOT DILUTE.

THIS HYDROGEN-PEROXIDE-BASED PRODUCT REMOVES MOLD STAINS THROUGH OXIDATION AND HIGH-FOAMING LIFT ACTION. MSR PRODUCES FOAM THAT CLINGS TO VERTICAL WALLS AND EVEN CEILINGS TO INCREASE DWELL TIME AND SHOW WHEN AFFECTED SURFACES HAVE BEEN TREATED.

DIRECTIONS:

- 1) HEPA vacuum surface.
- 2) Apply MSR with pump, trigger or airless sprayer or brush in sufficient volume to allow the surface to remain damp for at least 10 min. A pressure sprayer with pressure gauge and automatic pressure relief valve is recommended.
- 3) After foam has developed fully (3–5 minutes), agitate with a stiff bristled brush to help remove surface contaminants allowing MSR to penetrate deeper into the materials.
- 4) Allow MSR to dry fully.*
- 5) Remove loose organic material by HEPA vacuuming surface again.
- 6) For extended protection, apply OmniPro Mold Resistant Barrier to treated surfaces.

*A second application of MSR may be required to achieve desired results on heavily stained surfaces. Coverage rates 500–1,200 sq ft per gallon (coverage varies depending on the surface, application device and degree of staining present).

FOR BEST RESULTS:

Store product in cool location, away from sunlight and direct sources of heat. Keep container closed while not in use and protect contents from contamination.

CONTENTS:

Water (CAS 7732-18-5); ammonium hydroxide (CAS 1336-21-6); hydrogen peroxide (CAS 7722-84-1); anionic surfactant (CAS 119345-04-9)

© 2017 Made in U.S.A.
L.13128 Rev (A)



8 47136 00251 1