



Professional Products
Professional Results



3000

Masonry Block Filler

- Fills pores and small voids
- Eliminates pin holing
- Easy to apply, alkali resistant formula
- Not water sensitive after application

NET CONTENTS: 5 Gallons

For Professional Use Only

8330-5
White



CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

Calculated VOC: 77 g/l
FIBERLOCK IAQ 3000 8330
DANGER | DANGER



H319 - Causes serious eye irritation.
H317 - May cause an allergic skin reaction.
H350 - May cause cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.
H402 - Harmful to aquatic life.

H319 - Provoque une sévère irritation des yeux.
H317 - Peut provoquer une allergie cutanée.
H350 - Peut provoquer le cancer.
H372 - Risque avéré d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
H402 - Nocif pour les organismes aquatiques

Obtain special instructions before use.; Do not breathe dust/fume/gas/mist/vapours/spray.; Wear protective gloves/protective clothing/eye protection/face protection.; Use personal protective equipment as required.; Do not eat, drink or smoke when using this product.; Avoid release to the environment.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation.|Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols.|Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage.|Utiliser l'équipement de protection individuel requis.|Ne pas manger, boire ou fumer en manipulant ce produit.|Éviter le rejet dans l'environnement.|Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label); Wash contaminated clothing before reuse.; IF ON SKIN: Wash with plenty of soap and water.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; Get medical advice/attention if you feel unwell.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin.|Traitement spécifique (voir les conseils sur cette étiquette).|Laver les vêtements contaminés avant réutilisation.|EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon.|EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.|Consulter un médecin en cas de malaise.|Voir SDS pour la liste complète des phrases P

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

For Technical Information call 800.342.3755
These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 04.27.18

IAQ 3000 is a high quality, white, interior and exterior block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before top coating. IAQ 3000 contains mineral type fillers and fine mineral aggregates that fill voids in masonry surfaces. This 100% acrylic block filler is easy to apply, alkali resistant and provides a uniform surface capable of receiving all types of finish coats.

IAQ 3000 is ideal for application to masonry block, concrete, brick and stone. IAQ 3000 is not water sensitive after application and its flexibility and durability are the best available for a block filler, far superior to cementitious and PVA type formulations.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, efflorescence and other surface contamination. Nibs and mortar joints should be "bricked down" to remove all protrusions and mortar splatters. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWave RTU.

APPLICATION TOOLS

Apply IAQ 3000 with brush or roller. Spray application is not recommended because the mineral content is abrasive to spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer

PRODUCT APPLICATION

IAQ 3000 is supplied ready to use, but can be thinned sparingly with water for proper application consistency if necessary. IAQ 3000 should be applied full body, vertically and cross-hatched horizontally to remove all roller ridges and unevenness in the block filler. Brushing should be done with a short stubby brush, working the material well into any pinholes,

pores and voids. Material should be applied in horizontal sections with block mortar lines serving as a guide. Spray application is not recommended because the silica content is abrasive to spray equipment.

COVERAGE

200 ft²/gal. - average (varies with porosity of block)

DRYING TIME @ 70°F 50% R.H

To Touch: 4-8 hours
Recoat : 24 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 3000 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. Do not apply IAQ 3000 when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. IAQ 3000 will reduce seepage, but is not intended for use as a waterproofer. For waterproofing applications do not use IAQ 3000, use IAQ 9000 Mold-Resistant Waterproofer. IAQ 3000 should not be used as a finish coat or be allowed to weather for more than 60 days without being finish coated. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. Use adequate ventilation during application. This coating is not intended for use as a mold-resistant coating.