



Professional Products
Professional Results



9000

Mold Resistant Masonry Waterproofer*

- Holds back 10 PSI of water pressure
- Latex based formulation
- Tintable
- For interior or exterior use

*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

Calculated VOC: <100 g/l

FIBERLOCK IAQ 9000 8395
WARNING | ATTENTION



H302 - Harmful if swallowed.
H332 - Harmful if inhaled.
H319 - Causes serious eye irritation.
H351 - Suspected of causing cancer.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.; Do not breathe dust/fume/gas/mist/vapours/spray; Use only outdoors or in a well-ventilated area.; Use personal protective equipment as required.; Do not eat, drink or smoke when using this product.; Wear protective gloves/protective clothing/eye protection/face protection.; See SDS for full list of P phrases

IF exposed or concerned: Get medical advice/attention.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; If eye irritation persists: Get medical advice/attention.; IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.; IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.; Rinse mouth.; See SDS for full list of P phrases

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

8395-5 White



DANGER!

KEEP OUT OF REACH OF CHILDREN.

Do not take internally.
Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

H302 - Nocif en cas d'ingestion.
H332 - Nocif par inhalation.
H319 - Provoque une sévère irritation des yeux.
H351 - Susceptible de provoquer le cancer .
H361 - Susceptible de nuire à la fertilité ou au foetus .
H373 - Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.

Se procurer les instructions avant utilisation,|Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. |Utiliser seulement en plein air ou dans un endroit bien ventilé. |Utiliser l'équipement de protection individuel requis. |Ne pas manger, boire ou fumer en manipulant ce produit. |Porter des gants de protection/ des vêtements de protection/ un équipement de protection des yeux/ du visage. |Voir SDS pour la liste complète des phrases P

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin. |EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. |Si l'irritation oculaire persiste: consulter un médecin. |EN CAS D'INGESTION: appeler un CENTRE ANTIPOISON ou un médecin en cas de malaise. |EN CAS D'INHALATION: transporter la victime à l'extérieur et la maintenir au repos dans une position où elle peut confortablement respirer. |Rincer la bouche. |Voir SDS pour la liste complète des phrases P

IAQ 9000 is a white waterproofing coating that is specially formulated to stop water from penetrating through a variety of interior and exterior surfaces including above or below grade masonry walls, cinder and concrete blocks, stucco, brick, retaining walls, basements, and foundations. This latex based formula stops 10 psi of water pressure (greater than a wall of water 22 feet high). IAQ 9000 contains a fungistatic agent to resist mold growth on the surface of the coating. This fast-drying formula may be applied with a brush and/or roller on dry surfaces and cleans up easily with soap and water.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop and HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD(5323) or log on to www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWaveRTU.

Patch irregularities with an appropriate patching compound. Efflorescence, a white, powdery, crystal-like deposit visible on masonry surfaces, must be removed. Muriatic acid, used according to manufacturer's directions, is an effective efflorescence removal agent.

PRODUCT APPLICATION

STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN. For best results, use a 5 in. paddle wheel mixer, attached to a 1/2 horsepower, 1/2 inch electric drill. Coat surface only when air and surface temperatures are 50°F or higher. Apply IAQ 9000 directly on bare masonry. For best waterproofing results, wait for a dry (rain-free) period before application. Apply first coat with a good quality nylon bristle brush, working the waterproofer into the pores of the masonry - avoid excessive brushing. Allow to dry 3 hours before second coat. The second coat may be applied using brush, roller or spray. If leaking is still present after two coats, it indicates that pores or pinholes are still open. These areas should be coated again. Vent outside.

SPRAY APPLICATION

IAQ 9000 may be applied by spray to exterior and interior surfaces, providing certain precautions are followed. Specialized spray equipment is required, please refer to IAQ 9000 Spray Instructions sheet for specific details (Contact Fiberlock for more information). Do not attempt to apply

with conventional airless spray equipment due to the abrasive properties of IAQ 9000.

TINTING

May be tinted to light or pastel shades with alkali-proof universal tinting colors. Use only 25% of color normally recommended. Do not use more than 2 fl. oz. of colorant per gallon. IAQ 9000 is ideal as a finish coat.

COVERAGE

Smooth Surfaces:
1st coat: 100-125 ft²/gal.
2nd coat: 125 ft²/gal.
Porous Surfaces:
1st coat: 75 ft²/gal.
2nd coat: 125 ft²/gal.

DRYING TIME @ 70°F 50% R.H

To Touch: 1 hour
Recoat: 3 hours

CLEANUP

Clean application tools immediately after use in warm, soapy water. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Store locked up. Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. IAQ 9000 is resistant to the deteriorating action of mold and mildew. No claim is made for the preservative action other than to the coating film. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only. Dispose of contents/container to an approved waste disposal plant.