

IAQ 6040 is a low-viscosity, translucent violet, mold resistant sealant designed for use on new construction materials.* This specially formulated, water based coating contains a fungistatic agent to resist mold growth on the dry coating surface. The low-viscosity 100% acrylic formula is easy to apply, and the translucent finish will not block the appearance of coated building materials. IAQ 6040 can be applied to wood, OSB, wallboard, concrete and other construction materials.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWaveRTU.

APPLICATION TOOLS

Apply IAQ 6040 with brush, roller or airless spray equipment.

Brush: Synthetic, nylon or polyester bristle
Roller: Synthetic fiber 3/8" nap or longer
Spray: .015 to .021 tip @ 1500-2000 P.S.I.

PRODUCT APPLICATION

IAQ 6040 is supplied ready to use, but can be thinned sparingly with water (up to 8 oz. water per gallon) for proper application consistency if necessary. Apply one coat of IAQ 6040 generously and uniformly by airless spray or brush or roller to ensure that the finished surface is properly sealed. Two-coats may be required on some porous surfaces.

COVERAGE

Smooth Surfaces: 400-450 ft²/gal.
Porous Surfaces: 200-300 ft²/gal.

DRYING TIME @ 70°F 50% R.H

To Touch: 1-2 hours
Recoat: 8-16 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 6040 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. IAQ 6040 is resistant to the deteriorating action of mold and mildew. No claim is made for the preservative action to other than the coating film. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.



Professional Products
Professional Results



6040

Mold Resistant Sealant*

VIOLET

- Highly permeable

*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

Calculated VOC: 89 g/l

FIBERLOCK IAQ 6040 VIOLET 8363

WARNING | ATTENTION



H317 - May cause an allergic skin reaction.

H351 - Suspected of causing cancer.

H411 - Toxic to aquatic life with long lasting effects.



H317 - Peut provoquer une allergie cutanée.

H351 - Susceptible de provoquer le cancer.

H411 - Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.



Obtain special instructions before use.; Wear protective gloves/protective clothing/eye protection/face protection.; Use personal protective equipment as required.; Avoid breathing mist/vapours/spray.; Avoid release to the environment; Contaminated work clothing should not be allowed out of the workplace.; See SDS for full list of P phrases

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label); Wash contaminated clothing before reuse.; IF ON SKIN: Wash with plenty of soap and water.; If skin irritation or rash occurs: Get medical advice/attention.; Collect spillage.; See SDS for full list of P phrases

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin.|Traitement spécifique (voir les conseils sur cette étiquette).|Laver les vêtements contaminés avant réutilisation.|EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon.|En cas d'irritation ou d'éruption cutanée: consulter un médecin.|Recueillir le produit répandu.|Voir SDS pour la liste complète des phrases P

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

8363-5
Violet



8363-5

6 1 1 1 3 1 9 5 7 9 5 0