



Bonnet/Brush Encapsulate Cleaner

EncapuClean with Maxim

Complete soil encapsulator for brush and bonnet cleaning. A polymer barrier entraps soil for easy removal and retards future soiling.

Contents: One U.S. Gallon (3.79 Litres)

BRIDGEPOINT
SYSTEMS

- ✓ Residential Carpet
 - ✗ Commercial Carpet
 - ✗ Brush/Vacuum
 - ✗ Bonnet Cleaning
 - 7.5 RTU pH
- X = Primary Use ✓ = Secondary Use



CC08GL

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Go to www.bridgepoint.com/msds for additional safety, regulatory and liability information.

ENCAPUCLEAN WITH MAXIM PROVIDES

- Fast Drying • Deep Cleaning • Low VOC • Highly Concentrated • Soil Retarding • Stain Resistance • and a Neutral pH

Based on the newest technology in polymer surfactant cleaning, Encapuclean with Maxim cleans and absorbs the worst soil. The soil is absorbed into a bonnet or suspended for later vacuuming when used with brush method. Remaining residue retards resoiling and adds stain resistance. This makes vacuuming and spot cleaning more effective. Encapuclean with Maxim is the foundation for an excellent maintenance system for carpet. Hot water extraction is recommended on a semi-annual or annual basis.

INSTRUCTIONS

Dilute 1 to 16 (8 oz. per gallon hot water). To increase the effectiveness of the Maxim soil and stain resistance and for extreme cleaning, dilute 1 to 8 (16 oz. per gallon hot water). If any stiffness is noted on carpet after drying, vacuuming will normally remove it.

CAUTION

Keep out of reach of children. May cause skin and eye irritation, avoid contact with skin and eyes. Wear eye protection and gloves when mixing and using. Wash thoroughly after handling.

First Aid: In case of skin or eye contact, immediately flush with plenty of water. Get medical attention if irritation occurs.

Contents: Water (Cas #7732-18-5), Proprietary Surfactant/Polymer, Sodium Xylene Sulfonate (Cas# 1300-72-7), Glycol Ether DPNB (Cas# 29911-28-2), Proprietary Fluorochemical Blend



Application for brush and vacuum: Spray solution consistently over a section of carpet and brush in with rotary and carpet brush or counter rotating brush machine. It also can be applied with gravity feed tanks. Let dry overnight and extract with vacuum. For heavy soil, consider bonneting while carpet is damp.

Application for bonnet cleaning: Spray mixture lightly over an absorbent bonnet and then spray evenly over a section of the floor to be cleaned. Place bonnet under rotary machine and move over area until clean. Change bonnets frequently and place in plastic bag to keep moist until laundered. For use with medium to heavy soil.



Bonnet/Brush Encapsulate Cleaner

INSTRUCCIONES:

Diluya en una proporción de 1:16 (8 onzas por galón de agua caliente). Para aumentar la resistencia del Maxim a la suciedad y a las manchas, o para realizar una limpieza profunda, diluya en una proporción de 1:8 (16 onzas por galón de agua caliente). Si las fibras de la alfombra se quedan tiesas después de secarla, esto normalmente se elimina al limpiarla con la aspiradora.

Aplicación con disco de limpieza (bonnet): Rocíe la solución sobre un disco de limpieza (bonnet) absorbente, luego rocielo uniformemente sobre la sección del piso que va a limpiar. Coloque el disco bajo la máquina rotativa y páselo sobre el área hasta que esté limpia. Cambie de disco frecuentemente y colóquelos en una bolsa de plástico para que se mantengan húmedos hasta que se laven. Debe utilizarse si la alfombra está medianamente o muy sucia.

ENCAPUCLEAN WITH MAXIM



Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médicin si l'irritation se fait persistante.

SEE MATERIAL SAFETY DATA SHEET
VOIR LA FICHE SIGNATÉTIQUE

See Material Safety Data Sheet (MSDS):
www.bridgepoint.com/msds
for additional safety and regulatory information.

Ver al Material Safety Data Sheet (MSDS) en
www.bridgepoint.com/msds
para mas información de seguridad y reglas.

Another fine product from Bridgepoint Systems
4282 South 590 West, Salt Lake City, UT 84123
www.bridgepoint.com