




Heavy-Duty Traffic Lane Cleaner

Flex Low VOC

Flex some real muscle power in your cleaning. Flex Traffic Lane Cleaner is the most aggressive, effective and powerful prespray available. For professional use only.

Contents: One U.S. Gallon (3.79 Litres)



- X Commercial Carpet
- X Restoration
- ✓ Residential Carpet
- ✓ Hard Surface
- 12.5 RTU pH
- X = Primary Use ✓ = Secondary Use

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which

losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Go to www.bridgepoint.com/msds for additional safety, regulatory and liability information.



CC23GL

FLEX IS...

Strong: Flex will wrestle even the toughest soils off the carpet! Heavy greases, oils, and other tough soils are no match for Flex. Unequaled in the industry, Flex's surfactants, alkaline builders, and boosters come together to provide you with the toughest cleaner available.


Fast: Flex goes to work the second it comes in contact with soil in the carpet. High performance surfactants and boosters quickly suspend and emulsify even the most stubborn soils.

Economical: Even when purchasing small quantities, Flex offers you savings and power! Purchase Flex in larger quantities to save even more.

To be used as a traffic lane prespray on heavily soiled carpets. Should be extracted after use. Flex is not designed to be used on 5th generation fibers. Flex is designed for use in the Hydro-Force sprayer, electric sprayers, and other types of pump sprayer.

DIRECTIONS

For use with Hydro-Force sprayers: Add Flex directly to the 5 quart container. Dilute 1:32 to meet VOC standards in your state.



For Pump or Electric Sprayers: Dilute 1 part Flex to 32 parts hot water (4 oz. Flex to 1 gallon hot water) to meet VOC standards in your state.

For Extra Heavy Soil: Add 8 oz of Citrus-Solv to 5 quart container when using the Hydro Force. Add 1 ounce Citrus-Solv to each gallon of ready to use solution for other sprayer systems.

SAFETY INFORMATION

Caution: Pre-existing skin, eye and lung disorders may be aggravated by exposure. If product comes in contact with. **Eyes:** Flush with water for at least 15 minutes while holding eyelids open. Get medical attention. **Skin:** Flush skin with water. If irritation occurs, get medical attention. **Inhalation:** Remove victim to fresh air and seek medical attention.

Ingestion: Do not give anything by mouth if victim is unconscious. Give no more than two glasses of water, do NOT induce vomiting. Seek medical attention.

Contains: Water (CAS# 7732-18-5), Proprietary surfactant, STPP (CAS# 7758-29-4), Potassium Hydroxide (CAS# 1310-58-3), Ethylene Glycol Monobutyl Ether (CAS# 111-76-2)

Flex se debe utilizar como rocío preliminar en las áreas más transitadas de las alfombras excesivamente sucias. El producto se debe extraer después de su uso. Flex no ha sido diseñado para las fibras de quinta generación. Flex ha sido diseñado para su uso con el rociador Hydro-Force, con los rociadores eléctricos y con otros rociadores provistos de bomba.



Heavy-Duty Traffic Lane Cleaner

INSTRUCCIONES:

Para su uso con el rociador Hydro-Force: Agregue Flex directamente al recipiente de 5 cuartos de galón (aprox. 4.75 litros). Diluir en una proporción de 1 a 32 para cumplir con los estándares VOC en su Estado.

Para rociadores de bomba o eléctricos: Diluir 1 parte de Flex con 32 partes de agua caliente (4 onzas de Flex por galón de agua caliente) para cumplir con los estándares VOC en su Estado.

Para áreas extremadamente sucias: Añada 8 onzas (aprox. 237 ml) de Citrus-Solv al recipiente de 5 cuartos de galón cuando se usa el rociador Hydro-Force.

Para otras clases de rociadores: añada una onza de Citrus Solv a cada galón de solución lista para usarse (aprox. 8 ml por litro—1:128).

PRECAUCIÓN

Las afecciones de la piel, de los ojos y de los pulmones pueden empeorarse al exponerse a este producto. Si se produce contacto con los. **Ojos:** láveselos con bastante agua durante por lo menos 15 minutos, manteniendo abiertos los párpados, luego obtenga

atención médica. **Piel:** Lávese la piel con bastante agua. Si se produce irritación, obtenga atención médica. **Inhalación:** Saque a la víctima al aire fresco y obtenga atención médica. **Ingestión:** Si la víctima está inconsciente, no le dé nada por la boca. No le dé más de dos vasos de agua y NO induzca el vomito. Obtenga atención médica.

FLEX LOW VOC

May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

SEE MATERIAL SAFETY DATA SHEET
VOIR LA FICHE SIGNATÉTIQUE

See Material Safety Data Sheet (MSDS): www.bridgepoint.com/msds for additional safety and regulatory information.

Ver al Material Safety Data Sheet (MSDS) en www.bridgepoint.com/msds para mas información de seguridad y reglas.

Another fine product from Bridgepoint Systems
4282 South 590 West, Salt Lake City, UT 84123
www.bridgepoint.com