

# Q.C.T. with OxyBreak™

Peroxide Activated Quarry & Ceramic Tile and Concrete Cleaner and Brightener

QCT with OxyBreak™ is a synergistic combination of specialty surfactants, hydrogen peroxide, and D-Limonene that quickly cleans and brightens the grimest concrete, quarry tile, and ceramic tile and grout floors, fixtures, and walls.

HARD SURFACE

RTU pH 2.0-3.0

Quarry, Ceramic,  
Porcelain Tile,  
Finished, Stamped  
& Unfinished  
Concrete



If for any reason you are not thrilled with the performance of QCT with OxyBreak™, return it to your distributor and we'll get you a product that does.

Net Contents:  
One U.S. Gallon (3.78 liters)

Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.


QCT with OxyBreak™ is a synergistic combination of specialty surfactants, hydrogen peroxide, and D-Limonene that quickly cleans and brightens the grimest concrete, quarry tile, and ceramic tile and grout floors, fixtures, and walls. It safely lightens and brightens grout lines without leaving water marks or residue. You get the advantage of hydrogen peroxide's brightening power without the problems because it's stabilized! Add to that the activating and boosting effects that OxyBreak™ has on citrus solvents, and the solution penetrates every crack, crevice, and pore to emulsify and dissolve even the most stubborn soiling and grime. QCT with OxyBreak™ brightens grout without attacking and demineralizing unlike harsh acid based cleaners or chlorine bleach. It also self neutralizes so you don't need to worry about neutralizing the grout lines after cleaning and brightening them.

QCT with OxyBreak™ will work effectively with the hard surface attachments for the RX-20 Rotary Extractor, as well as rotary and stationary hard surface cleaning wands. It also can be safely and effectively used with virtually any hard surface floor cleaning brush or mop system.

Contents: Alcohol Ethoxylate (CAS# 63439-46-3); 2-Propanol, 1-Methoxyethanol (CAS#107-98-2); Hydrogen Peroxide (CAS# 7722-84-1); D-Limonene (CAS# 5989-27-5); Water (CAS# 7732-18-5)

## Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For normal soiling, mix 32 ounces (1 quart) of solution with a gallon of warm or hot water (1:4) into a professional spray applicator. For heavy soiling, mix 64 ounces (two quarts) of solution with a gallon of warm or hot water into a professional spray applicator. For application through a standard injection sprayer, mix one quart water with four quarts of solution into 5 quart container.
3. Apply mixed solution evenly in an overlapping pattern across the surface to be cleaned. You can also apply mixed solution with a damp mop, sponge or other professional application equipment. If using a mop for solution application and surface cleaning, change your mop water often to make sure that the soil is not re-deposited.
4. Allow solution to dwell for 2-10 minutes. Agitate grout lines with grout brush if needed.
5. For best cleaning and brightening results, agitate and extract cleaning solution using hot water and a RX20 equipped with hard surface cleaning attachments or a rotary extraction tool. In tight spaces, or on sensitive surfaces and floors with loose grout, use a stationary hard surface cleaning wand or simply mop with rinse water. Rinse the area thoroughly and allow to dry.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.
7. Rinse sprayer used for solution application with water thoroughly after each use.



Lot:

Read the  
MSDS  
Scan here



## Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
2. En caso de suciedad normal, mezclar 32 onzas (un cuarto) de solución con un galón de agua tibia o caliente (1:4) en un aplicador de aerosol profesional. En caso de suciedad fuerte, mezclar 64 onzas (dos cuartos) de la solución con un galón de agua tibia o caliente en un aplicador de spray profesional. Para la aplicación a través de un pulverizador de inyección estándar, mezclar un litro de agua con cuatro litros de solución en un recipiente cuarto 5.
3. Aplicar solución mezclada uniformemente en un patrón superpuesto a través de la superficie a limpiar. También puede aplicar una solución mixta con un trapeador húmedo esponja u otro equipo de aplicación profesional. Si se utiliza un trapeador para la aplicación y solución de limpieza de la superficie, cambie el agua del trapeador con frecuencia para asegurarse de que el suelo no se vuelvan a depositar.
4. Deje que la solución a habitar durante 2-10 minutos. Agitar las líneas de lechada con brocha lechada si es necesario.
5. Para obtener los mejores resultados de limpieza y abrillantado, agitar y extraer la solución de limpieza con agua caliente y un RX20 equipado con accesorios de limpieza de superficies duras o una herramienta de extracción rotativo. En espacios reducidos, o sobre superficies sensibles y pisos con lechada suelta, use una vara estacionario limpieza de superficies duras o simplemente limpiar con agua de enjuague. Enjuague bien el área y deje que se seque.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, el aire centrífugo o de corriente descendente después de la limpieza.
7. Enjuague pulverizador utilizado para la aplicación de solución con agua después de cada uso.

## Precautions and First Aid:

Keep out of reach of children. Contact may cause skin and eye irritation. Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form. Use only in well ventilated areas. In case of eye contact, immediately flush with plenty of water. If irritation persists, seek medical attention. In case of skin irritation, flush with plenty of water. If ingested, drink large quantities of water and seek medical attention. Remove to fresh air in case of inhalation. See Material Safety Data Sheet (MSDS): [www.hydrmaster.com/msds](http://www.hydrmaster.com/msds) for additional safety and regulatory information.

## Precauciones y Primeros Auxilios:

Mantener fuera del alcance de los niños. El contacto puede causar irritación cutánea y ocular. Use guantes y gafas de seguridad al manejar para evitar cualquier contacto con los ojos y el contacto con la piel en forma de concentrado. Use sólo en áreas bien ventiladas. En caso de contacto con los ojos, lávelos inmediatamente con abundante agua. Si la irritación persiste, busque atención médica. En caso de irritación de la piel, lavar con abundante agua. Si se ingiere, beber grandes cantidades de agua y busque atención médica. Sacar al aire libre en caso de inhalación. Ver Hoja de Seguridad (MSDS): [www.hydrmaster.com/MSDS](http://www.hydrmaster.com/MSDS) para mayor seguridad y normativas.



HydraMaster  
[www.hydrmaster.com](http://www.hydrmaster.com)  
425.775.7272

Part # 950-155-S Art 950-155-S-R1



8 10149 01032 3