

Stain ABSORB



Absorbent Stain Lifter

Stain Absorb

A Highly absorbent powder used to correct wicking and pull stains from fabric and carpet

BRIDGEPOINT
SYSTEMS

This product is sold by weight and not volume. During shipping and handling, some settling may occur.


Contents: 2 Pounds (.91 Kilograms)

- X Residential Carpet
 - X Commercial Carpet
 - X Upholstery
 - X Floor & Fire Restoration
- N/A RTU pH
- X = Primary Use ✓ = Secondary Use

IMPORTANT NOTICE TO PURCHASER: The manufacturer and seller warrant that the chemical contained herein conforms to its standard specifications. Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages



CS25A



Stain absorb may be used as a last-effort spotting procedure for wicking, residue and mineral stains which have not responded to other spotting methods.

Directions:

1. Pre-clean and extract stained area (wet clean only).
2. Apply stain absorb over entire stain with a thickness of 1/8" to 1/4".
3. Leave for 8 to 24 hours.
4. Remove powder & dry vacuum.
5. Re-clean and apply as needed

Note: use this product in conjunction with wet cleaning only! Do not use with solvent cleaning!

Safety information

Caution: this product contains amorphous diatomaceous earth and varying percentages of crystalline silica.

Avoid prolonged inhalation of dust. A respirator is recommended over extended periods of exposure to dust.

Stain absorb se puede usar como un procedimiento de ultimo recurso para manchas de color café, residuos o manchas de minerales que no responden a otros métodos para quitar manchas.

Instrucciones:

1. Haga una limpieza preliminar y extraiga lo que pueda del área manchada (con agua solamente).
2. Aplique una capa de 1/8 a 1/4 de pulgada (1/3 a 2/3 cm) de stain absorb en toda la mancha.
3. Deje reposar el producto durante un período de 8 y 24 horas.
4. Quite el polvo y limpie con una aspiradora en seco.
5. Vuelva a limpiar y a aplicar el producto, según sea necesario.

Nota: ¡utilice este producto solamente al limpiar con agua! ¡No lo utilice con solventes de limpieza!

Información sobre la seguridad

Precaución: este producto contiene diatomita amorfa y un porcentaje variable de sílice cristalina. Evite la inhalación prolongada de los polvos. Si se hace necesario exponerse a los polvos durante períodos extensos, se recomienda el uso de un respirador.

Mode d'emploi:

1. Faire un nettoyage préliminaire et extraire ce que vous pouvez de la surface tachée (avec de l'eau seulement).
2. Appliquer une couche de 1/8 à 1/4 de pouces (1/3 à 2/3 cm) d'épaisseur de stain absorb sur toute la surface de la tache.
3. Laisser agir entre 8 et 24 heures.
4. Enlever la poudre et aspirer à sec.
5. Rénover et réappliquer le produit si nécessaire.

Attention: ce produit contient de la terre de diatomées amorphe et divers pourcentages de sílice cristalline. Éviter l'inhalation prolongée de la

poussière. On recommande l'utilisation d'un respirateur pendant les périodes prolongées d'exposition à la poussière.

STAIN ABSORB

SEE MATERIAL SAFETY DATA SHEET -

VOIR LA FICHE SIGNATÉTIQUE



May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, flush immediately with plenty of water, then seek medical advice if the irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

See Material Safety Data Sheet (MSDS): www.bridgepoint.com/msds for additional safety and regulatory information.

Ver al Material Safety Data Sheet (MSDS) en www.bridgepoint.com/msds para mas información de seguridad y reglas.

Another fine product from Bridgepoint Systems
542 W. Confluence Ave., Salt Lake City, UT 84123
www.bridgepoint.com