

# WOOD MATTE finish

## Wood Finish - Matte

Hydro-Force Wood Finish is a one-component water based maintenance finish for hardwood floors, cabinets and furniture. It is highly resistant to traffic, wear and scuffing. It is also resistant to water and to household chemicals. It is the ideal maintenance finish for all hardwoods in both residential and commercial settings.

Contents: One U.S. Gallon (3.79 Litres)



A Maintenance Finish for :


- ✗ Hardwood Floors
- ✓ Cabinets
- ✓ Furniture

✗ = Primary Use ✓ = Secondary Use



CW033GL

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to [www.hydroforce.com/msds](http://www.hydroforce.com/msds) for additional safety, regulatory and liability information.



Under normal residential conditions a wood floor should be cleaned and refinished with two coats of Hydro-Force Wood Finish at least every two years. It should be done each year under heavy traffic conditions. Hydro-Force Wood Finish should not be used as a primary finish. If floors are either new or must be sanded down to bare wood, Hydro-Force Wood Finish should not be used. Use it only as a maintenance topcoat where an existing primary coat of quality finish has already been applied.

### DIRECTIONS:

- Clean:** Before finishing a floor or other hardwood surface first clean surface with Hydro-Force Wood cleaner. Scrub the surface with a maroon pad or equivalent to remove soil, damaged finish and to affect a slight amount of abrasion that allows Hydro-Force Wood Finish to adhere to the surface. Follow the directions on the Wood Cleaner Label. More details may be found in the Hydro-Force Wood Products Training Manual.
- Repair Damaged Areas:** Repair scratches, gouges or other damage to the wood surface with Hydro-Force Wood Patch. Refer to the Wood Products training manual and video for directions.
- Finish the Hardwood Surface:** Once the floor or other surface is properly prepared, it is ready to be finished with Hydro-Force Wood Finish. Shake well before each use. For floors, pour a pool of the product about the size of a saucer on the floor. Spread the finish in an even coat over the floor with the Hydro-Force Applicator and fitted terry-cloth pad. Continue to pour and spread the product until an even coating has been applied over the entire area. Allow at least 30 minutes for drying and apply another coat in the same fashion. You may judge drying

visually. Allow about 10 additional minutes for drying after the surface appears dry.

**Cabinets and Furniture Surface:** Apply finish with a soft lint free cloth. Use latex or rubber gloves to keep finish from bonding to hands. Finish should be applied in a lighter coat than is needed for a floor application. A third coat of finish may be needed for an acceptable appearance.

**Fire and Water Damage Restoration:** Hydro-Force's Wood Finish is a greater sealer/finish to use after a fire or smoke damage, sealing in odors while adding a new protective finish. Hydro-Force's Wood Finish can be used after water losses to restore small surface checks while adding a new surface finish. Clean floor, cabinets and furniture with your normal restoration cleaners. A final surface cleaning is needed with Hydro-Force Wood Cleaner to neutralize and prep the surface. Apply finish as directed above.

**Coverage:** Approximately 1,000 sq. feet per gallon.

- The floor may be walked on without shoes after drying for 1 - 2 hours.
- Furniture may be replaced after 24 hours. Rugs may be replaced after three days.

### SAFETY INFORMATION

- Keep out of reach of children.
- Do not allow to freeze.
- Avoid direct contact with eyes. In case of eye contact, immediately remove contact lenses and flush eyes for 15 minutes. If ingested, drink plenty of water or milk and call your physician.

**CONTAINS:** Water, Polyester Acrylate, Butylglycol (112-34-5), N-Methyl-2-Pyrrolidone (872-504)

**INSTRUCCIONES:** No debe ser utilizado como un barniz primario.

**1. Limpie:** Antes de poner barniz al piso o piso de madera, limpie la superficie con Hydro-Force Wood Cleaner. Talla la superficie con una almohadilla 3M marrón o equivalente para quitar la tierra o barniz dañado, y de este modo el producto Hydro-Force Wood Finish puede adherirse a



la superficie. Sigue las instrucciones en la etiqueta de Wood Cleaner. Mas Detalles puedan ser encontrados en el Manual de Entrenamiento de Hydro-Force Wood Products.

**2. Para reparar áreas dañadas:** Para reparar rasguños, grietas u otro daño a la superficie de la madera con Hydro-Force Wood Match. Refiérase al manual y video de entrenamiento de Wood Products para instrucciones.

**3. Para superficies barnizadas:** Una vez que el piso u otra superficie son preparados apropiadamente, estarán listos para aplicar Hydro-Force Wood Finish. Agite bien antes de cada uso. Para pisos, vierta una pequeña cantidad del producto más o menos del tamaño de un plato. Esparza el barniz en una capa constante sobre el piso con el Hydro-Force Aplicador y un pedazo de tela. Continúe poniendo y esparciendo el producto hasta que quede parejo toda el área. Deje por lo menos 30 minutos para que se seque y aplique otra capa de la misma manera.

**Superficies de gabinetes y muebles:** Aplique el barniz con un trapo que no tenga pelusa. Use unos guantes de plástico para que no se manche sus manos de barniz. El barniz debe ser aplicado con capas delgadas. La tercera capa de barniz tal vez se necesitara según como se vea.

**Restauración para superficies dañadas por fuego y agua:** Hydro-Force Wood Finish es un gran sellador de barniz para ser usado después de danos de fuego o humo, mientras se pone un barniz protector para sellar olores. Brigepoint Wood Finish puede ser usado después de un daño causado por agua en la madera, y para restaurar grietas poniendo barniz nuevo. Para limpiar pisos, gabinetes y muebles use limpiadores de restauración normales,

limpie el lugar lo mejor que pueda donde va a hacer usado Hydro-Force Wood Cleaner. Ponga e producto como se menciona arriba.

### INFORMACIÓN DE SEGURIDAD:

- Manténgase fuera del alcance de los niños.
- No permite que se congele
- Evite contacto directo en los ojos. En caso de contacto visual, quitase inmediatamente los lentes y pongase agua en los ojos por 15 minutos. Si se ingiere tome bastante agua y llame a su medico.

## WOOD FINISH - MATTE

SEE MATERIAL SAFETY DATA SHEET -

VOIR LA FICHE SIGNATÉTIQUE

May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.



Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

- See Material Safety Data Sheet (MSDS): [www.HydroForce.com/msds](http://www.HydroForce.com/msds) for additional safety and regulatory information.
- Ver al Material Safety Data Sheet (MSDS) en [www.HydroForce.com/msds](http://www.HydroForce.com/msds) para mas información de seguridad y reglas.
- Another fine product from Hydro-Force Systems 4282 S 590 W, Salt Lake City, UT 84123 [www.HydroForce.com](http://www.HydroForce.com)