

zerorez®



Premium Fiber Protector



RTU pH: 4.0 - 6.0

Contents: 1 US Gallon (3.79 Litres)

determine the suitability of this product for the intended use, and user assumes all risk and liability whatsoever in connection therewith. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

IMPORTANT NOTICE TO PURCHASER: The manufacturer and seller warrant that the chemical contained herein conforms to its standard specifications. Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, user shall

ZEROREZ PREMIUM FIBER PROTECTOR provides the absolute latest and most advanced technology in fluorochemical and acid dye resistors (dye-blockers) for maximum stain prevention and enhanced soil resistance. Unlike many branded protectors, Premium Fiber Protector contains all of the same treatments that carpet mills use to provide protection to new stain resistant carpet. The fluorochemicals increase surface tension allowing soil to be easily vacuumed off. The acid-dye blockers in Premium Fiber Protector help prevent staining from common household food spills.

ZEROREZ PREMIUM FIBER PROTECTOR

- Low moisture application results in carpets drying quicker
- Excellent penetration on wet or dry carpet
- Fluorochemical & Stain Resist Technology
- Freeze Thaw Stable
- Suitable for use on upholstery, wool carpets or rugs

DIRECTIONS

WATER KEY



- Dilute by mixing 1 part concentrate protector with 2 parts water.
- Application: Apply to freshly cleaned carpet using an electric or battery powered sprayer maintaining 35 to 50 psi with an 8004 or 8005 TeeJet nozzle. Apply evenly over entire carpet surface. Brush or rake the carpet.
- Coverage: 400 to 800 sq ft per diluted gallon for damp or dry carpet. Coverage depends on carpet pile density; i.e. heavy pile residential requires 1 RTU gallon per 400 sq ft, low pile commercial requires 1 RTU gallon per 800 sq ft.
- If accidental freezing occurs, allow to thaw at room temperature, then shake vigorously.

CONTENTS

Water (Cas # 7732-18-5), Acrylic Copolymer Partially Fluorinated Urethane Polymer Phenolic Resin Condensate.



D082GL V2

WARNING

Keep out of reach of children.



HAZARD STATEMENTS:

Causes eye irritation.

PRECAUTIONARY STATEMENTS:

IF IN EYES: Rinse cautiously with water for several minutes. Remove Contact Lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF SKIN irritation occurs: Get medical advice/attention.

12577 South 265 West, Suite 3A
Draper, UT 84020 | 866-937-6739

www.zerorez.com